

> PRINT

ECOSYS P2040dn ECOSYS P2040dw

BLACK AND WHITE A4 DESKTOP PRINTER

THE FEATURE-RICH A4 PRINT PROFESSIONALS



If you're looking for a fast, reliable and versatile A4 black and white printer, you really can't go wrong with the ECOSYS P2040dn and P2040dw. Boasting fast first print times and speeds of up to 40ppm, duplex and network and Wi-Fi as standard* alongside high paper capacities these devices will simplify your workflows with ease. Not only that, these devices incorporate long-life, energy-efficient components, providing low Total Cost of Ownership and making them the reliable printers you would expect from KYOCERA, enabling you to remain productive at all times.

*ECOSYS P2040dw only.



Environmental print features

Duplex print mode (Double sided printing), N-Up printing mode (N pages on 1 sheet), Toner save mode (Draft print mode), Quiet mode (reduced print speed).

KYOCERA NetViewer

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

ECOSYS P2040dn/ECOSYS P2040dw GENERAL

Technology: KYOCERA ECOSYS Laser

Control panel: 2 line LCD back lit display

Engine speed: Up to 40 pages A4 per minute Print resolution: 300 dpi, 600 dpi, 1200 dpi

Duty cycle:

Maximum: 50,000 pages per month Maximum Average: 3,333 pages per month Average: 2,000 pages per month

Warm-up time: Approx. 15 seconds or less

Time to first print: Approx. 6.4 seconds or less CPU: 800MHz

Memory: Standard 256 MB, max. 256 MB

Standard interface:

ECOSYS P2040dn: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Slot for optional SD/SDHC-Card ECOSYS P2040dw: USB 2.0 (Hi-Speed), USB Host Interface,

Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Wireless LAN, Slot for optional SD/SDHC-Card

Dimensions (W x D x H): Main unit: 375 x 393 x 272 mm

Weight: Main unit: Approx. 14 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption: Printing: 620 W Ready mode: 8 W Sleep mode: 0.8 W

Noise (Sound pressure level: ISO 7779/ISO 9296):

Printing: 48.8 dB(A) LpA Ready/Standby mode: Immeasurably low Sleep mode: Immeasurably low

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray; $60 - 220 \text{ g/m}^2$; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm - 216 x 356 mm) 250-sheet universal cassette; $60 - 163 \text{ g/m}^2$; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 - 216 x 356 mm). Max. input capacity with options: 850 sheets

Duplex functionality as standard: Double-sided printing: 60 – 163 g/m²; A4, A5, B5, Letter, Legal

Output capacity: Max. 250 sheet face down

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc

Emulations: PCL 6 (PCL 5e/PCL-XL), PostScript 3 (KPDL 3), PDF Direct Print, XPS/OpenXPS

Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request

Fonts/barcodes: 93 scalable fonts for PCL6/KPDL3, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

Integrated accounting: 20 department codes

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752

Toner-Kit TK-1160: toner yield 7,200 pages A4 Starter toner: toner yield 3,600 pages A4

Command Center RX

The Command Center RX enables to control and manage various settings by accessing the device via Web browser.

USB Host Interface for USB Flash Memory

Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

Application-based Profiles

The KX printer driver can create a direct link between dedicated applications and predefined or customised print profiles. You can set that all documents from a user or an application be printed with activated duplex mode as standard, thus leading to a reduced paper consumption.

OPTIONS


PF-1100 Paper feeder (max. 2 units): 250 sheets; 60 – 163 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm – 216 x 356 mm) **UG-33:** ThinPrint support

USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available **CB-1100:** Wooden cabinet

WARRANTY

2-year warranty as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 100,000 pages A4 (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.





KYOCERA Document Solutions (UK) Ltd, Eldon Court, 75-77 London Road, Reading RG1 5BS Tel: 0118 931 1500, Fax: 0118 931 1108 www.kyoceradocumentsolutions.co.uk, info@duk.kyocera.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

YOUR KYOCERA BUSINESS-PARTNER

